NSN 5955-00-233-2567

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-233-2567

| Overall Length: |
|---|
| Between 0.998 inches and 1.023 inches |
| Terminal Length: |
| Between 0.223 inches and 0.248 inches |
| Overall Width: |
| 0.757 inches |
| Body Length: |
| 0.775 inches |
| Body Width: |
| 0.725 inches |
| Body Thickness: |
| 0.317 inches |
| Overall Thickness: |
| 0.352 inches |
| Terminal Diameter: |
| Between 0.048 inches and 0.052 inches |
| Mode Of Oscillation: |
| Fundamental |
| Circuit Resonance: |
| Series resonance |
| Specified Frequency: |
| 200.000 kilohertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.478 mils and 0.494 centimeters |
| Drive Level Rating: |
| Between 1.6 milliwatts and 2.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.010/+0.010 |
| Equivalent Resistance Value In Ohms: |
| 2500.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-3098/7 government specification |

N/a

Shelf Life:

NSN 5955-00-233-2567

Quartz Crystal Unit - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0