## **NSN 5955-00-238-1852**Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-238-1852  |
|--|
| Overall Length:  |
| Between 1.907 inches and 1.937 inches  |
| Terminal Length:   |
| Between 0.625 inches and 0.655 inches  |
| Overall Width:   |
| 1.170 inches   |
| Body Length:   |
| 1.282 inches   |
| Overall Thickness:   |
| 0.411 inches   |
| Terminal Diameter:   |
| Between 0.123 inches and 0.127 inches  |
| Mode Of Oscillation:   |
| Fundamental  |
| Circuit Resonance:   |
| Antiresonance  |
| Load Capacitance In Picofarads:  |
| Between 34.5 and 35.5  |
| Specified Frequency:   |
| 8.115 megahertz  |
| Holder Cover Material:   |
| Plastic  |
| Operating Tempurature Range:   |
| -55.0/+90.0 degrees celsius  |
| Center To Center Distance Between Terminals:   |
| 0.490 mils and 0.510 centimeters   |
| Drive Level Rating:  |
| Between 27.0 milliwatts and 33.0 milliwatts  |
| Frequency Tolerance For Operating Tempurature In Percent:  |
| -0.005/+0.005  |
| Equivalent Resistance Value In Ohms:   |
| 30.0   |
| Style Designator:  |
| Rectangular body, pin terminals  |
| Test Data Document:  |
| 81349-mil-c-16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental        |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  |
| Specification Data:  |
| 81349-mil-c-16 government specification  |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

## NSN 5955-00-238-1852

Quartz Crystal Unit - Page 2 of 2



Demilitarization:

No

Fiig:

A059a0

Mil-std (military Standard):

Mil-c-16 spec.