NSN 5955-00-243-7704

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-243-7704

Overall Length:

1.774 inches

Terminal Length:

0.238 inches

Overall Width:

0.757 inches

Body Length:

1.526 inches

Body Width:

0.725 inches

Body Thickness:

0.317 inches

Overall Thickness:

0.352 inches

Terminal Diameter:

0.050 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 20.0 and 19.5 and 20.5

Shunt Capacitance In Picofarads:

4.1

Specified Frequency:

89.500 kilohertz

Holder Cover Material:

Metal

Operating Tempurature Range:

-40.0/+70.0 degrees celsius

Center To Center Distance Between Terminals:

0.486 inches

Drive Level Rating:

0.1 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.012/+0.012

Equivalent Resistance Value In Ohms:

90000.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-243-7704

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

