NSN 5955-00-246-8916

Quartz Crystal Unit - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5955-00-246-8916

1.774 inches
Terminal Length:
0.238 inches
Overall Width:
0.757 inches
Body Length:
1.526 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 20.0 and 19.5 and 20.5
Shunt Capacitance In Picofarads:
4.2
Specified Frequency:
86.500 kilohertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+70.0 degrees celsius
Center To Center Distance Between Terminals:
0.486 inches
Drive Level Rating:
0.1 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.012/+0.012
Equivalent Resistance Value In Ohms:
90000.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-milc3098/18 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-246-8916

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0