## NSN 5955-00-249-0744

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-249-0744

Overlands           0.800 inches           0.800 inches           Between 0.192 inches and 0.217 inches           0.750 inches           0.750 inches and 0.217 inches           0.750 inches           0.750 inches           0.750 inches and 0.583 inches           0.750 inches and 0.583 inches           0.750 inches		
Famial Length:         Reveen 0.192 inches and 0.217 inches         Overlithet         Oxal With:         1.30 inches         Body Length:         Reveen 0.656 inches and 0.583 inches         Body With:         1.30 inches         0.370 inches         0.370 inches         0.370 inches         0.370 inches         0.315 inches         0.316 inches         1.316 inches <td< td=""><td>Overall Length:</td><td></td></td<>	Overall Length:	
Between 0.192 inches         Orgal Widh:         0.750 inches         Between 0.565 inches and 0.583 inches         Between 0.565 inches and 0.583 inches         Body Widh:         0.720 inches         0.720 inches         0.720 inches         0.730 inches         0.731 inches         0.740 inchess:         0.740 inchess         0.740 inches         0.740 in termines         0.740 in termines	0.800 inches	
Nevral With:0.750 incles9.760 incles9.760 incles and 0.583 incles9.760 incles and 0.583 incles9.720 incles <td>Terminal Length:</td> <td></td>	Terminal Length:	
750 inches         9750 inches         960y Length:         8etween 0.685 inches and 0.583 inches         960y Width:         0.720 inches         960y Thickness:         0.730 inches         900y Hinkenss:         0.345 inches         0.345 inches         0.345 inches         0.345 inches         0.345 inches and 0.052 inches         Mode Of Oscillation:         Fernical Diamete:         Retween 0.048 inches and 0.052 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antresonance         Partical State on Picofarads:         Between 27.5 and 26.5         Specified Frequency:         Audret Cover Material:         Noder Cover Material:         Noder Cover Material:         Mode Cover Material:         Valor Resistance Value In Pincytarute In Percent:         9.0007/e0.007         Equivaler Resistance Value In Ohms:         9.001         9.012         9.021         9.021         9.021         9.021         9.021         9.021         9.021	Between 0.192 inches and 0.217 inches	
Body Length:         Bedy Length:         Between 0.565 inches and 0.583 inches         Body Uidht:         0.720 inches         Body Length:         Body Length:         Oxfor Inches         Perverent Oxfor Inches         Oxfor Inches         Specified Frequency:         You Frequency Toerante	Overall Width:	
Beaveen 0.565 inches and 0.583 inches         Body Widh:         0.720 inches         Body Thickness:         0.315 inches         Overall Thickness:         0.345 inches         Body Mickness:         0.345 inches         Body Body Body Body Body Body Body Body	0.750 inches	
Body With:0.720 inches0.720 inchesBody Thickness:0.315 inches0.345 inches0.345 inches0.345 inches0.345 inches0.345 inches0.345 inches1000 Outsillation:1000 Outsillation:1010 Ou	Body Length:	
20         Porticitiones         0.315 inches         Overall Thickness:         0.345 inches         0.345 inches         Between 0.48 inches and 0.052 inches         Between 0.48 inches and 0.052 inches         Mode Of Oscillation:         Fundamental         Chrout Resonance:         Antiresonance         Between 0.48 inchersand 0.052 inches         Severen 0.48 inchersand 0.052 inches         Antiresonance         Load Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahert2         Holder Cover Material:         Metal         Optimizer Range:         19.0478.0 diagrees celsius         Chrote Cover Distance Between Terminals:         10.478 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         10.007         Chrote Distance Between Terminals:         10.01         10.01         Specified Tolenes (For Operating Tempurature In Percent:         10.02         Equivalent Resistance Value In Ohms:         10.02         Sup Obelgination:         10.02         Syle D	Between 0.565 inches and 0.583 inches	
Rody Trickness:0.315 inches0.varall Trickness:0.345 inches0.345 inches0.345 inchesTerminal Diameter:0.406 or Oscillation:RotamentalCircuit Resonance:AndresonanceAnder Partice StratesBetween 27.5 and 28.5Specified Frequency:A.0741 megahertzHorder Cover Material:Norder StratesPacting Engene StratesAnder Cover Material:Audie Cover Distance Between Terminals:Audie Cover Distance Cover Co	Body Width:	
0.315 inchesOverall Thickness:0.345 inches0.345 inchesTerminal Diameter:Between 0.048 inches and 0.052 inchesModer O Scillation:FundamentalCorcut Resonance:AntiresonanceAndiresonance:Specified Frequency:7.40741 megahertzHoter Over Material:Operating Tompurature Range:6.50.0485.0 degrees celsiusChriter Detarted Sector7.40741 megahertzBourden Core Material:0.4076 mils and 0.496 centimeters7.40741 megahertz10.4076 mils and 0.496 centimeters10.4076 mils and 0.496 centimeters10.407710.4078 mils and 0.496 centimeters10.4078 mils and 0.496 centimeters10.407910.407910.407010.407010.407010.407010.407010.407010.407010.407010.407010.407010.407010.407010.407010.407011.401116836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification former, excludes commercial catalogs, industry directories, and similar trade publications, reflecting uper alt up data end endertal10.40400 commercial catalogs, industry directories, and similar trade publications, reflecting up end alt up data end endertal10.40400 commercial catalogs, industry directories, and similar trade publications, reflecting up end alt up data end endertal10.40400 commercial catalogs, industry	0.720 inches	
Overall Thickness:         0.345 inches         Terminal Diameter:         Between 0.048 inches and 0.052 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Andersonance:         Antiresonance         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Mote Cover Material:         Mote Cover Material:         Mote Cover Material:         A0.0428 in d.948 centimeters         Poperating Tempurature Range:         +50.0485.0 degrees celsius         Center To Center Distance Between Terminals:         0.0476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Eyluvalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Coval body, pin terminals         Body, pin terminals         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Style Designator:         Style Designator      <	Body Thickness:	
Construction         Construction         Between 0.048 inches         Between 0.048 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         : A10741 megahertz         Holder Cover Material:         Metal         Operating Tempurature Range:         : 50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.475 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         : 0.007/+0.007         Equivalent Resistance Value In Ohms:         : 0.00         Style Designator:         Cival body, pin terminals         Text Data Document:         : 8149-milc18836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	0.315 inches	
Familan Diameter:         Between 0.048 inches and 0.052 inches         Hode Of Oscillation:         Fundamental         Fundamenta         Circuit Resonance:         Antiresonance         Lodd Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Motel         Operating Tempurature Range:         14004 So degrees celsius         Conter Distance Between Terminals:         14747 milis and 0.496 centimeters         Frequency Tolerance Tolemating Tempurature In Percent:         14708 Output         14709 Output         14709 Output         14700 Output         14700 Output         14700 Output         14700 Output         15000 Output         15010 Output         15020 Output         15030 Output         15040 Output         15040 Output erminals         15040 Output	Overall Thickness:	
Between 0.048 inches and 0.052 inches         Mode Of Oscillation:         Fundamental         Encuit Resonance:         Antiresonance         Ded Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Notes         Posting Tempurature Range:         +0.04785.0 degrees celsius         Conter To Center Distance Between Terminals:         Postoper To Center Distance Between Terminals:         0.4070.007         Equivalent Resistance Value In Ohms:         5.0.0         Stop Designator:         Oval body, pin terminals         Guards Terminals         Stop Designator:         Stop Designator:         Stabel Appendic Rations (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on centaria	0.345 inches	
Mode Of Oscillation:FundamentalCircuit Resonance:AntiresonanceLoad Capacitance In Picofarads:Between 27.5 and 28.5Specified Frequency:7.40741 megahentzHolder Cover Material:NetalOperating Tempurature Range:+ 50.0/+85.0 degrees celsiusConter To Center Distance Between Terminals:0.4074 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:- 0.007/+0.007Equivalent Resistance Value In Ohms:- 50.0Style Designator:- 10.0Style Designator:- 10.0Style Designator:- 10.0- 10.0Style Designator:- 10.0 <td>Terminal Diameter:</td> <td></td>	Terminal Diameter:	
Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Metal         Operating Tempurature Range:         +50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Total Document:         10.412         Style Designator:         10.423         Style Designator:         10.424         Style Designator:         10.424         Style Designator:         10.424         Bitade-mile16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Between 0.048 inches and 0.052 inches	
Circuit Resonance: Antiresonance Antiresonance Circuit Resonance Circuit Resonance Code Code Netofarads: Between 27.5 and 28.5 Specified Frequency: 7.40741 megahertz Holder Cover Material: Holder Cover Mate	Mode Of Oscillation:	
Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 7.40741 megahertz Holder Cover Material: Holder	Fundamental	
Load Capacitance In Picofarads:         Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Metal         Operating Tempurature Range:         +50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Test Data Document:         81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain	Circuit Resonance:	
Between 27.5 and 28.5         Specified Frequency:         7.40741 megahertz         Holder Cover Material:         Holder Cover Material:         Metal         Operating Tempurature Range:         +50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Stole Designator:         Oval body, pin terminals         Forst Data Document:         1048         Stady-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Antiresonance	
Specified Frequency:7.40741 megahertzHolder Cover Material:Holder Cover Material:MetalOperating Tempurature Range:+ 50.0/+85.0 degrees celsiusConter To Center Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:50.0Syle Designator:Oval body, pin terminalsTest Data Document:61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Load Capacitance In Picofarads:	
7.40741 megahetz Holder Cover Material: Metal Derating Tempurature Range: +50.0/+85.0 degrees celsius Conter To Center Distance Between Terminals: Conter To Center Distance Between Terminals: A476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: A0.407 +0.007 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Aval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Between 27.5 and 28.5	
Holder Cover Material:         Metal         Operating Tempurature Range:         +50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Toxal Document:         81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain	Specified Frequency:	
Metal         Operating Tempurature Range:         +50.0/+85.0 degrees celsius         Center To Center Distance Between Terminals:         0.476 mils and 0.496 centimeters         Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Test Data Document:         81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	7.40741 megahertz	
Operating Tempurature Range:+50.0/+85.0 degrees celsiusCenter To Center Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:50.0Style Designator:Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationformat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Holder Cover Material:	
+50.0/+85.0 degrees celsius Center To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Metal	
Center To Center Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:50.0Style Designator:Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (ore trained or trai	Operating Tempurature Range:	
0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	+50.0/+85.0 degrees celsius	
Frequency Tolerance For Operating Tempurature In Percent:         -0.007/+0.007         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Oval body, pin terminals         Test Data Document:         81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (precipies, and similar trade publications, reflecting general type data on certain)	Center To Center Distance Between Terminals:	
-0.007/+0.007 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.476 mils and 0.496 centimeters	
Equivalent Resistance Value In Ohms: 50.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Frequency Tolerance For Operating Tempurature In Percent:	
50.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	-0.007/+0.007	
Style Designator:         Oval body, pin terminals         Test Data Document:         81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Equivalent Resistance Value In Ohms:	
Oval body, pin terminals <b>Test Data Document:</b> 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	50.0	
<b>Test Data Document:</b> 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Style Designator:	
81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Oval body, pin terminals	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Test Data Document:	
	81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	

## Shelf Life:

N/a

## NSN 5955-00-249-0744

Quartz Crystal Unit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A059a0

