## NSN 5955-00-250-8374

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-250-8374

| Overall Length:  |  |
|--|--|
| 0.800 inches   |  |
| Terminal Length:   |  |
| Between 0.192 inches and 0.217 inches  |  |
| Overall Width:   |  |
| 0.750 inches   |  |
| Body Length:   |  |
| Between 0.565 inches and 0.583 inches  |  |
| Body Width:  |  |
| 0.720 inches   |  |
| Body Thickness:  |  |
| 0.315 inches   |  |
| Overall Thickness:   |  |
| 0.345 inches   |  |
| Terminal Diameter:   |  |
| Between 0.048 inches and 0.052 inches  |  |
| Mode Of Oscillation:   |  |
| Fundamental  |  |
| Circuit Resonance:   |  |
| Antiresonance  |  |
| Load Capacitance In Picofarads:  |  |
| Between 27.5 and 28.5  |  |
| Specified Frequency:   |  |
| 5.33906 megahertz  |  |
| Holder Cover Material:   |  |
| Metal  |  |
| Operating Tempurature Range:   |  |
| +50.0/+85.0 degrees celsius  |  |
| Center To Center Distance Between Terminals:   |  |
| 0.476 mils and 0.496 centimeters   |  |
| Frequency Tolerance For Operating Tempurature In Percent:  |  |
| -0.007/+0.007  |  |
| Equivalent Resistance Value In Ohms:   |  |
| 75.0   |  |
| Style Designator:  |  |
| Oval body, pin terminals   |  |
| Test Data Document:  |  |
| 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |  |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain        |  |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                          |  |
|  |  |

## Shelf Life:

N/a

## NSN 5955-00-250-8374

Quartz Crystal Unit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A059a0

