NSN 5955-00-251-2374

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-251-2374

Overall Length: 0.800 inches 0.800 inches Derminal Length: Between 0.192 inches and 0.217 inches Overall Width: 0.750 inches Oxford inches Dody Length: Between 0.565 inches and 0.583 inches Dody Width: 0.720 inches Dody Width: 0.720 inches Dody Thickness: 0.315 inches Overall Thickness: 0.345 inches Overall Thickness: 0.345 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Occillation: Fordamental Creuit Resonance Anticesonance Lead Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.430 dregateriz Holder Cover Material: Verait Thickness 0.475 mils and 0.496 contimeters Frequency Tolerance For Operating Tempurature In Percent: 0.4074 for Mils and 0.496 contimeters Frequency Tolerance For Operating Tempurature In		
Fernial Length: Retween 0.192 inches and 0.217 inches Overlithet Orsoll Mich: Orsoll Mich: Orsoll Mich: Retween 0.565 inches and 0.583 inches Body Length: Rotween 0.565 inches and 0.583 inches Orsoll Mich: Profestion: Orsoll Mich: Orsoll Mich:	Overall Length:	
Between 0.192 inches Overall With: 0.750 inches Between 0.555 inches and 0.583 inches Between 0.555 inches and 0.583 inches Body With: 0.720 inches 0.720 inches 0.720 inches 0.730 inches 0.731 inches 0.740 inchesses: 0.745 inches 0.746 inches and 0.052 inches Between 0.484 inches and 0.052 inches 740 ind megateriz 740 inches and 0.052 inches 740 ind sub date 740 inches and 0.452 inches 740 inches and 0.452 inches 740 inches and 0.452 inches 740 inches ano	0.800 inches	
Nevral With:0.750 inches804 (Jungh):804 wean 0.565 inches and 0.583 inches804 With:0.720 inches804 With:0.720 inches804 With:0.720 inches804 With:0.720 inches804 With:0.720 inches804 With:0.720 inches904 With:0.720 inches904 With:0.720 inches904 With:0.720 Wit	Terminal Length:	
0730 inches 0740 inches 0540 inches and 0.583 inches 0540 inches and 0.583 inches 0540 inches 0720 inches 0730 inches 0540 inches 0540 inches 0540 inches 0540 inches 0540 inches 0540 inches 0541 inches 0540 inches 0550 inches 0560 inches 0560 inches 0570 inches 0560 inches 0570 inches 0570 inches 0560 inches 0570 inches 0570 inches 0580 inches and 0.052 inches 0560 inches 0560 inches 0560 inches 0561 inches 0570 inches 0561 inches 0561 inches 0570 inches 0580 inches and 0.052 inches 0561 inches 0570 inches 0570 inches 0561 inches 0570 inches 0570 inches 0580 inches and 0.052 inches <t< td=""><td>Between 0.192 inches and 0.217 inches</td><td></td></t<>	Between 0.192 inches and 0.217 inches	
Body Length: Bedween 0.565 inches and 0.583 inches Body Width: 0.720 inches Body Ticknoss: 0.315 inches Overall Thickness: 0.345 inches Body Ticknoss: 0.345 inches Body Ticknoss: 0.345 inches Body Ticknoss: 0.345 inches Body Collation: Body Collation: Forein Resonance: Nationance Body Collation:	Overall Width:	
Between 0.585 inches and 0.583 inches Body Width: 0.720 inches Body Thickness: 0.315 inches Overall Thickness: 0.345 inches 0.345 inches 0.345 inches 0.345 inches 0.345 inches 0.445 inches and 0.052 inches Mode Of Oscillation: Pundamental Circult Resonance: Antiresonance Particesonance: Antiresonance Policy Partice Partice Abde Gapacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: A:3404 megahert2 Bolder Cover Material: Modes Polytick Big degrees celsuis Conter Distance Between Terminals: A:156 Mis and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: 4:000740.007 Equivalent Resistance Value In Ohms: 7:0 Syle Designator: 7:0 Syle Designator: 7:0 Syle Designator: 10:1 Syle	0.750 inches	
Body Width: 0.720 inches Body Thickness: 0.345 inches Overall Thickness: 0.345 inches Overall Thickness: 0.345 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.430 megahertz Holder Cover Material: Volder Cover Material: Poorting Tempurature Range: +500 (#85.0 degrees celsius Center To Center Distance Between Terminals: -0.007 #0.007 Fequency Toleance For Operating Tempurature In Percent: -0.007.40.07 Stol Besignator: 7.50 Style Besignator: 7.61 Style Besignator: 7.62 Style Besignator: 7.63 Style Besignator: 7.64 Style Besignator: 7.64 Style Besignator:	Body Length:	
0.20 Proceeding Proceeding 0.315 inches 0.315 inches Overall Thickness: 0.345 inches 0.345 inches Proceeding Between 0.045 inches and 0.052 inches Mode Of Oscillation: Fundamental Chrouit Resonance Antiresonance Dadapacitance In Picofarads: Severen 0.25.5 Specified Frequency: 5.4304 megahertz Holder Cover Material: Note 10 Posting Tenguenstenee 5.4304 megahertz Posting Tenguenstenee 6.4304 megahertz Posting Tenguenstenee 6.3004 Severen Distance Between Terminals: 6.3004 Severen Severen Terminals: 6.3004 Severen Kord Distance Between Terminals: 6.3007 Holder 7.300000 Equivalent Resistance Value In Ohms: 7.30 Stol Designator: 7.30 Stol Designator: 7.30 Stol Designator: 6.3004, pin terminals Courted Severeification (Between 0.565 inches and 0.583 inches	
Bdy Thickness: 0.315 Inches Overall Thickness: 0.345 Inches 0.345 Inches Bruinal Diameter: Between 0.048 Inches and 0.052 Inches Mod Of Oscillation: Fundamental Furdamental Carcuit Resonance: Ander Gazacitance In Picofardas: Between 27.5 and 28.5 Specified Frequency: A3404 meghetrz Hoter Picolards Resonance Avol 20.5 Between 27.5 and 28.5 Between 27.5 and 28.5 Pacified Frequency: A3404 meghetrz Hoter Cover Material: Notel Avol 80.6 degrees celsius Conter Distance Between Terminals: Avol 70.0007 Erquency Tolerance For Operating Tempurature In Percent: Avol 70.007 Englesentaria Avol 70.007 Stol Bedignation: Avol 70.007 Stol Bongmate: Avol 70.007 Stol Bongmate: Avol 70.007 Stol Bongmate: Avol 70.007	Body Width:	
0.315 inches 0.345 inches 0.345 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Pindamental Grout Resonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.4304 megahertz Hoter Poreting Tempurature Range: 6.50.0425.0 degrees celsius Chere Naterial: 6.307.0420 Porting Tempurature Range: 6.307.0420 Chere Naterial: 7.007.0420 Pareting Seguesting Tempurature In Percent: 6.307.04007 Explored Seisgiantor: 7.007 Stolder, pin terminals 7.01 Stolder, pin terminals 7.02 Stolder, pin terminals 7.03 Stolder, pin terminals 7.04 Stolder, pin terminals 7.05 Stolder, pin terminals 7.07 Stolder, pin terminals 7.07 <td>0.720 inches</td> <td></td>	0.720 inches	
Overall Thickness:0.436 inches0.436 inchesTerminal Diameter:Between 0.048 inches and 0.052 inchesMode Of Oscillation:PundametalChrout Resonance:AntiresonanceLacd Capacitance In Picofarads:Between 27.5 and 28.5Specified Frequency:3.4304 megahetzHolder Cover Material:Holder Cover Material:6.0426.5 degrees celsiusChrout Polance Between Terminals:0.4376. mills and 0.496 centimeters7.0071/0.007Equivalent Resistance Value In Ohnes:7.00Sylder Disperiation:7.00Sylder Disperiation:7.00Sylder Disperiation:7.01Sylder Disperiation:7.02Sylder Disperiation:7.03Sylder Disperiation:7.04Sylder Disperiation:7.05Sylder Disperiation:7.06Sylder Disperiation:7.07Sylder Disperiation:7.08Sylder Disperiation:7.09Sylder Disperiation:7.01Sylder Disperiation:7.02Sylder Disperiation:7.03Sylder Disperimention:7.04Sylder Disperimention:7.05Sylder Disperimention:7.07Sylder Disperimention:7.077.087.097.097.097.097.09 <t< td=""><td>Body Thickness:</td><td></td></t<>	Body Thickness:	
0.345 inches Permianl Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.4304 megahert2 Holder Cover Material: Motal Operating Tempurature Range: + 50.0/+85.0 degrees celsius Catter To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters + 70.007 Equivation Resistance Value In Ohms: - 0.0071+.007 Equivation Resistance Value In Ohms: - 0.007 Stol Polosignator: - 0.0071+.007 Stol Polosignator: - 0.0071+	0.315 inches	
Ferninal Diameter: Between 0.048 inches and 0.052 inches Hode Of Oscillation: Fundamental Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.4304 megahertz Holder Cover Material: Metal Operating Tempurature Range: 4.50.0458.0 degrees celsius Conter Distance Between Terminals: 6.476 mills and 0.496 centimeters Frequency Tolerance Toolmentating Tempurature In Percent: -0.007/0.007 Equivalent Resistance Value In Ohms: 7.5.0 Stole Deginator: 7.6.0 Stole Deginator: 7.6.1 Stole Deginator: 6.10.1 Stole Deginator: 7.5.0 Stole Deginator: 1.5.0 Stole Deginator: 1.5.0 Stole Deginator: 1.5.0 Stole Deginator: 1.5.0 Stole Degination: 1.5.0	Overall Thickness:	
Between 0.048 inches and 0.052 inches Mode Of Oscillation: Fundamental Bruicesonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.4304 megahertz Holder Cover Material: Motal Posting Tempurature Range: +50.0/#85.0 degrees celsius Conter Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/0.007 Equivalent Resistance Value In Ohms: 7.5.0 Syle Designator: Out course Fata Document 7.5.0 State Document 7.5.0 State Document 6.1349-spicification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting engent but end endertions	0.345 inches	
Mode Of Oscillation:FundamentalCircuit Resonance:AntiresonanceLad Capacitance In Picofarads:Between 27.5 and 28.5Specified Frequency:5.4304 megahertzHolder Cover Material:NotalOperating Tempurature Range:+50.0/+85.0 degrees celsiusConter To Center Distance Between Terminals:0.476 mils and 0.496 centimeters+Foquency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:7.5.0Style Designator:Oval body, pin terminalsTotal Document:1349-mile 16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formet; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification formet; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification	Terminal Diameter:	
Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: 5.4304 megahertz Holder Cover Material: Metal Operating Tempurature Range: +50.0/+85.0 degrees celsius Center To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Totat Document: 10430-yin iterminals 75.0 Style Designator: 10431 Test Data Document: 10430-yin iterminals 10430-yin iterminals 10440-yin iterminals	Between 0.048 inches and 0.052 inches	
Circuit Resonance: Antiresonance Antiresonance Circuit Resonance Return Resonance Circuit Resonance Ci	Mode Of Oscillation:	
Antiresonance Load Capacitance In Picofarads: Between 27.5 and 28.5 Specified Frequency: S4304 megahertz S4304 megahertz Holder Cover Material: Holder Cover Mat	Fundamental	
Load Capacitance In Picofarads:Between 27.5 and 28.5Specified Frequency:5.4304 megahertzHolder Cover Material:Holder Cover Material:MetalOperating Tempurature Range:+50.0/+85.0 degrees celsiusCenter To Senter Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:75.0Style Designator:Oval body, pin terminalsCourder Diston Courder Co	Circuit Resonance:	
Between 27.5 and 28.5Specified Frequency:5.4304 megahertzHolder Cover Material:Holder Cover Material:MetalOperating Tempurature Range:+50.0/+85.0 degrees celsiusCenter To Center Distance Between Terminals:Ot476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:75.0Style Designator:Oval body, pin terminalsTert Data Document:1349-milc16836 specification (includes engineering type bulletins, brochures, tend treffect specification type data on certain1349-milc16836 specification (includes engineering type bulletins, brochures, tend treffect specification type data on certain	Antiresonance	
Specified Frequency:5.4304 megahertzFolder Cover Material:Holder Cover Material:MetalOperating Tempurature Range:+ 50.0/+85.0 degrees celsiusCenter To Center Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:- 0.007/+0.007Equivalent Resistance Value In Ohms:75.0Style Designator:Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	Load Capacitance In Picofarads:	
5.4304 megahertz Holder Cover Material: Metal Derating Tempurature Range: +50.0/+85.0 degrees celsius Center To Center Distance Between Terminals: Center To Center Distance Between Terminals: Cater To Center Distance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Coval body, pin terminals Coval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Between 27.5 and 28.5	
Holder Cover Material:MetalOperating Tempurature Range:+50.0/+85.0 degrees celsiusCenter To Center Distance Between Terminals:O.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:75.0Style Designator:Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain	Specified Frequency:	
Metal Operating Tempurature Range: +50.0/+85.0 degrees celsius Center To Center Distance Between Terminals:Outer To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (metal catalogs, industry directories, and similar trade publications, reflecting general type data on certain	5.4304 megahertz	
Operating Tempurature Range:+50.0/+85.0 degrees celsiusCenter To Center Distance Between Terminals:0.476 mils and 0.496 centimetersFrequency Tolerance For Operating Tempurature In Percent:-0.007/+0.007Equivalent Resistance Value In Ohms:75.0Style Designator:Oval body, pin terminalsTest Data Document:81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification61349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	Holder Cover Material:	
+50.0/+85.0 degrees celsius Center To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Metal	
Center To Center Distance Between Terminals: 0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Operating Tempurature Range:	
0.476 mils and 0.496 centimeters Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	+50.0/+85.0 degrees celsius	
Frequency Tolerance For Operating Tempurature In Percent: -0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain (includes engineering type bulletins)	Center To Center Distance Between Terminals:	
-0.007/+0.007 Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.476 mils and 0.496 centimeters	
Equivalent Resistance Value In Ohms: 75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (prediction data in specification data in specification data on certain data)	Frequency Tolerance For Operating Tempurature In Percent:	
75.0 Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	-0.007/+0.007	
Style Designator: Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Equivalent Resistance Value In Ohms:	
Oval body, pin terminals Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	75.0	
Test Data Document: 81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Style Designator:	
81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Oval body, pin terminals	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Test Data Document:	
	81349-milc16836 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in	specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data of	on certain
	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	

Shelf Life:

N/a

NSN 5955-00-251-2374

Quartz Crystal Unit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

