# NSN 5955-00-259-3710

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-259-3710

## **Overall Length:**

1.023 inches

### **Terminal Length:**

Between 0.223 inches and 0.248 inches

# **Overall Width:**

0.757 inches

#### **Body Length:**

0.775 inches

#### **Body Width:**

0.725 inches

#### Body Thickness:

0.317 inches

#### **Overall Thickness:**

0.352 inches

#### Terminal Diameter:

Between 0.048 inches and 0.052 inches

#### Mode Of Oscillation:

Third overtone and fifth overtone

#### Circuit Resonance:

Series resonance

#### Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

41.083333 megahertz

#### Frequency Stability In Percent:

-0.00025/+0.00025

#### **Controlled Reference Temp:**

75.0 degrees celsius

#### **Operable Tempurature Range:**

-55.0/+90.0 degrees celsius

#### Holder Cover Material:

Metal or glass

#### **Operating Tempurature Range:**

+70.0/+80.0 degrees celsius and -55.0/+90.0 degrees celsius

#### **Center To Center Distance Between Terminals:**

0.478 mils and 0.494 centimeters

#### **Drive Level Rating:**

Between 0.8 milliwatts and 1.2 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001 and -0.003/+0.003

#### Equivalent Resistance Value In Ohms:

40.0

# NSN 5955-00-259-3710

Quartz Crystal Unit - Page 2 of 2



# Style Designator:

Square body

# Test Data Document:

81349-mil-c-3098/62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/43d government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A059a0