NSN 5955-00-269-5868

Quartz Crystal Unit - Page 1 of 2



| Overall Length: Between 0.998 inches and 1.023 inches Terminal Length: Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: 0.775 inches Body Width: 0.775 inches Body Width: 0.725 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: Between 31.5 and 32.5 |
|--|
| Terminal Length: Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: 0.775 inches Body Width: 0.725 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Between 0.223 inches and 0.248 inches Overall Width: 0.757 inches Body Length: 0.775 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Overall Width: 0.757 inches Body Length: 0.775 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| 0.757 inches Body Length: 0.775 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Body Length: 0.775 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| 0.775 inches Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Body Width: 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| 0.725 inches Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Body Thickness: 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| 0.317 inches Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Overall Thickness: 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| 0.352 inches Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Terminal Diameter: Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Between 0.048 inches and 0.052 inches Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Mode Of Oscillation: Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Third overtone Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Circuit Resonance: Antiresonance Load Capacitance In Picofarads: |
| Antiresonance Load Capacitance In Picofarads: |
| Load Capacitance In Picofarads: |
| |
| Retween 31.5 and 32.5 |
| Detween 51.5 and 52.5 |
| Shunt Capacitance In Picofarads: |
| 12.0 |
| Specified Frequency: |
| 21.3035 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.478 mils and 0.494 centimeters |
| Drive Level Rating: |
| Between 31.5 milliwatts and 32.5 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 24.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification. |

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-269-5868

Quartz Crystal Unit - Page 2 of 2



| Spec | ifica | ation | Data: |
|------|-------|-------|-------|
|------|-------|-------|-------|

81349-mil-c-3098/14 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0