

View Online at <https://aerobasegroup.com/nsn/5955-00-420-0815>

Overall Length:

Between 0.919 inches and 1.000 inches

Overall Height:

Between 0.175 inches and 0.200 inches

Overall Width:

0.922 inches

Environmental Protection:

Moisture proof and shock resistant and vibration

Vibration Resistance Range In Hertz:

+100.0/+2000.0

Vibration Resistance Amplitude:

20.0 gravitational units

Shock Resistance Rating In Gravitational Units:

100.0

Operating Temperature Range:

-55.0/+100.0 degrees celsius

Storage Temperature Range:

-65.0/+130.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

73.333 megahertz 2nd output channel err-100 and 83.333 megahertz 2nd output channel err-100

Frequency Adjustment Type:

Continuous

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Pin bottom

Connection Contact Type And Quantity:

15 pin external

External Dc Operating Voltage In Volts:

0.0 2nd voltage err-100 and 12.0 2nd voltage err-100

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A32200