## NSN 5955-00-433-5895

Quartz Crystal Unit - Page 1 of 2

**Overall Length:** 

40.0



View Online at https://aerobasegroup.com/nsn/5955-00-433-5895

1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Third overtone and fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
7.0
Specified Frequency:
Specified Frequency:
Specified Frequency: 43.250 megahertz
Specified Frequency: 43.250 megahertz Frequency Stability In Percent:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal or glass
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal or glass Operating Tempurature Range:
Specified Frequency:  43.250 megahertz  Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 85.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: -70.0/+80.0 degrees celsius
Specified Frequency:  43.250 megahertz  Frequency Stability In Percent: -0.00025/+0.00025  Controlled Reference Temp: 85.0 degrees celsius  Operable Tempurature Range: -55.0/+90.0 degrees celsius  Holder Cover Material:  Metal or glass  Operating Tempurature Range: -70.0/+80.0 degrees celsius  Center To Center Distance Between Terminals:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal or glass Operating Tempurature Range: -70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal or glass Operating Tempurature Range: -70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters Drive Level Rating:
Specified Frequency: 43.250 megahertz Frequency Stability In Percent: -0.00025/+0.00025 Controlled Reference Temp: 85.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal or glass Operating Tempurature Range: -70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.478 mils and 0.494 centimeters Drive Level Rating: Between 0.8 milliwatts and 1.2 milliwatts

## NSN 5955-00-433-5895

Quartz Crystal Unit - Page 2 of 2



Desig	

Tube body, wire leads

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0