

View Online at https://aerobasegroup.com/nsn/5955-00-437-3673

Overall Length:6.110 inchesOverall Height:0.781 inchesOverall Width:2.700 inchesOperating Tempurature Range:-20.0/+85.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareIdentification Designator:25vs0e-15423Inclosure Type:OpenOperating Control Method:AutomaticInstallation Design:MechanicalCircuit Construction Type:Solid stateFrequency Per Channel:1.000 kilohertz output channelImpedance Rating Per Channel:1.000 kilohertz output channelExternal Dc Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUit of Measure:Penilitarization:Yes - demil/mliFig:Langen	
Overall Height:0.781 inchesOverall Width:2.700 inchesOperating Tempurature Range:-20.0/+85.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareIdentification Designator:25vs0e-15423Inclosure Type:OpenOperating Control Method:AutomaticInstallation Design:MechanicalCircuit Construction Type:Solid stateFrequency Per Channel:1.000 kilohertz output channelImpedance Rating Per Channel:1.000 kilohers output channelExternal De Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUnit Of Measure:-*Demilitarization:Yes - demil/mliFlig:	Overall Length:
0.781 inches Overall Width: 2.700 inches Operating Tempurature Range: -20.0/+85.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 7.0.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohersoutput channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Sheff Life: N/a Unit Of Measure: Temilitarization: Yes - demil/mli Fiig:	6.110 inches
Overall Width:2.700 inchesOperating Tempurature Range:-20.0/+85.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareIdentification Designator:25vs0e-15423Inclosure Type:OpenOperating Control Method:AutomaticInstallation Design:MechanicalCircuit Construction Type:Solid stateFrequency Per Channel:1.000 kilohertz output channelImpedance Rating Per Channel:1.000 kilohens output channelExternal Dc Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUit Of Measure:Fig:	Overall Height:
2.700 inches 2.700 inches Operating Tempurature Range: -20.0/+85.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	0.781 inches
Operating Tempurature Range: -20.0/+85.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 1.000 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Totation Complement Va Demilitarization: Yes - demil/mli	Overall Width:
-20.0/+85.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: To0.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	2.700 inches
Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 1.000 kilohertz output channel Impedance Rating Per Channel: 1.000 kiloherts output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Sheff Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli	Operating Tempurature Range:
Not rated Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 1.000 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	-20.0/+85.0 degrees celsius
Basic Shape Style: Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 1.000 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Average Life Measurement:
Rectangular or square Identification Designator: 25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Not rated
Identification Designator:25vs0e-15423Inclosure Type:OpenOperating Control Method:AutomaticInstallation Design:MechanicalCircuit Construction Type:Solid stateFrequency Per Channel:70.0 kilohertz output channelImpedance Rating Per Channel:1.000 kilohms output channelExternal Dc Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUnit Of Measure:Permilitarization:Yes - demil/mliFiig:	Basic Shape Style:
25vs0e-15423 Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Rectangular or square
Inclosure Type: Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: 	Identification Designator:
Open Operating Control Method: Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: To.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Yes - demil/mli	25vs0e-15423
Operating Control Method:AutomaticInstallation Design:MechanicalCircuit Construction Type:Solid stateFrequency Per Channel:70.0 kilohertz output channelImpedance Rating Per Channel:1.000 kilohms output channelExternal Dc Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUnit Of Measure:Solititarization:Yes - demil/mliFiig:	Inclosure Type:
Automatic Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Tempilitarization: Yes - demil/mli Fiig:	Open
Installation Design: Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Temilitarization: Yes - demil/mli Fiig:	Operating Control Method:
Mechanical Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Automatic
Circuit Construction Type: Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Installation Design:
Solid state Frequency Per Channel: 70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: //a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Mechanical
Frequency Per Channel:70.0 kilohertz output channelImpedance Rating Per Channel:1.000 kilohms output channelExternal Dc Operating Voltage In Volts:28.0 single voltageFsc Application Data:Receiving set, countermeasuresShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	Circuit Construction Type:
70.0 kilohertz output channel Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli Fig:	Solid state
Impedance Rating Per Channel: 1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Femilitarization: Yes - demil/mli Fig:	Frequency Per Channel:
1.000 kilohms output channel External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	70.0 kilohertz output channel
External Dc Operating Voltage In Volts: 28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Impedance Rating Per Channel:
28.0 single voltage Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1.000 kilohms output channel
Fsc Application Data: Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	
Receiving set, countermeasures Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	28.0 single voltage
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	-
Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	
 Demilitarization: Yes - demil/mli Fiig:	
Yes - demil/mli Fiig:	Unit Of Measure:
Yes - demil/mli Fiig:	
Fiig:	
100000	
A32200	A32200