## NSN 5955-00-444-6606

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-444-6606

Overall Length:
1.738 inches
Terminal Length:
0.238 inches
Overall Width:
0.750 inches
Body Length:
1.500 inches
Body Width:
Between 0.715 inches and 0.722 inches
Body Thickness:
Between 0.310 inches and 0.317 inches
Overall Thickness:
0.350 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
32.0
Specified Frequency:
100.000 kilohertz
100.000 kilohertz Holder Cover Material:
Holder Cover Material:
Holder Cover Material: Metal
Holder Cover Material: Metal Operating Tempurature Range:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 5000.0
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 5000.0 Style Designator:
Holder Cover Material: Metal Operating Tempurature Range: -40.0/+70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 2.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005/+0.005 Equivalent Resistance Value In Ohms: 5000.0 Style Designator: Oval body, pin terminals

---

## NSN 5955-00-444-6606

Quartz Crystal Unit - Page 2 of 2

Demilitarization:

No

Fiig:

A059a0

