## NSN 5955-00-448-0303

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-448-0303 **Overall Length:** 21.375 inches **Overall Height:** 7.500 inches **Overall Width:** 19.000 inches **Vibration Resistance Range In Hertz:** Not rated **Individual Section Quantity: Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** +0.0 to 50.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** O464src-80058 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Manual **Installation Design:** Top of cabinet/counter **Control Type:** Local **Circuit Construction Type:** Electron tube Frequency Per Channel: 1.0 megahertz 5th output channel Frequency Adjustment Type: Stepped **Individual Step Frequency:** 125.0 hertz and 250.0 hertz and 500.0 hertz and 1000.0 hertz **Attenuation In Decibels:** 

Not rated

**Average Power Rating Per Channel:** 

100.0 milliwatts output

## NSN 5955-00-448-0303

Noncrystal Controlled Oscillator - Page 2 of 2



Signal Voltage Rating Per Channel:
2.500 volts output
Overall Gain:
Not rated
Impedance Rating Per Channel:
500.000 ohms 6th output channel
Indicator Device Type And Quantity:
1 meter
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Receptacle, power rear
Operating Ac Frequency In Hertz:
60.0 single voltage and 400.0 single voltage
Connection Contact Type And Quantity:
3 receptacle, power internal
External Ac Operating Voltage In Volts:
115.0 single voltage
Phase:
Single
Fsc Application Data:
Radio, except navigation, nonairborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200