Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-454-8705

Overall Length:
2.000 inches
Overall Height:
0.750 inches
Overall Width:
1.875 inches
Environmental Protection:
General purpose
Vibration Resistance Range In Hertz:
+21.0 to 400.0
Vibration Resistance Amplitude:
9.0 gravitational units
Shock Resistance Rating In Gravitational Units:
75.0
Operating Tempurature Range:
-40.0 to 175.0 degrees fahrenheit
Average Life Measurement:
Not rated
Basic Shape Style:
Irregular
Maximum Operating Altitude Rating:
10000.0 feet
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Local
Circuit Construction Type:
Solid state
Frequency Per Channel:
9.145 gigahertz operating channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
12.0 milliwatts output
Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated

Crystal Controlled Oscillator - Page 2 of 2



Impedance Rating Per Channel:

Not rated

Maximum Continuous Operating Time In Hours:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, coaxial bottom

Connection Contact Type And Quantity:

3 receptacle, coaxial external

External Dc Operating Voltage In Volts:

15.0 single voltage

Criticality Code Justification:

Bhtb

Test Data Document:

19200-10549175 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200