

NSN 5955-00-476-6331 Crystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-00-476-6331 **Overall Length:** 1.000 inches **Overall Height:** 0.630 inches **Overall Width:** 1.000 inches **Environmental Protection:** Moisture proof and shock resistant and vibration **Vibration Resistance Range In Hertz:** +50.0/+2000.0 **Vibration Resistance Amplitude:** 20.0 gravitational units **Shock Resistance Rating In Gravitational Units:** 100.0 **Operating Tempurature Range:** -55.0/+115.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 534328-2-96214 **Maximum Operating Altitude Rating:** 100000.0 feet **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic

Installation Design:

Module

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

11.0432 megahertz operating channel

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Pin bottom

NSN 5955-00-476-6331

Crystal Controlled Oscillator - Page 2 of 2



Connection Contact Type And Quantity:
3 pin external
External Dc Operating Voltage In Volts:

-5.2 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200