# NSN 5955-00-483-1618

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-483-1618

# **Overall Length:**

Between 1.749 inches and 1.774 inches

# **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.757 inches

## **Body Length:**

1.526 inches

#### **Body Width:**

0.725 inches

## Body Thickness:

0.317 inches

## **Overall Thickness:**

0.352 inches

#### **Terminal Diameter:**

Between 0.048 inches and 0.052 inches

# Mode Of Oscillation:

Fundamental

## **Circuit Resonance:**

Series resonance

# Shunt Capacitance In Picofarads:

6.1

#### **Specified Frequency:**

29.000 kilohertz

# Holder Cover Material:

Metal

# **Operating Tempurature Range:**

-40.0/+70.0 degrees celsius

# Center To Center Distance Between Terminals:

0.476 mils and 0.496 centimeters

#### **Drive Level Rating:**

0.1 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.012/+0.012

# **Equivalent Resistance Value In Ohms:**

100000.0

# Style Designator:

Oval body, pin terminals

# **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-c-3098/28 government specification

# NSN 5955-00-483-1618

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

