NSN 5955-00-493-1060

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-493-1060

Overal	I Length:

Between 0.723 inches and 0.773 inches

Terminal Length:

Between 0.625 inches and 0.655 inches

Overall Width:

1.170 inches

Body Length:

Between 0.500 inches and 0.515 inches

Body Width:

Between 0.394 inches and 0.402 inches

Body Thickness:

0.411 inches

Overall Thickness:

0.460 inches

Terminal Diameter:

Between 0.038 inches and 0.042 inches

Mode Of Oscillation:

Fundamental

Circuit Resonance:

Antiresonance

Load Capacitance In Picofarads:

Between 34.5 and 35.5

Specified Frequency:

6.380 megahertz

Holder Cover Material:

Metal

Operating Tempurature Range:

-55.0/+90.0 degrees celsius

Center To Center Distance Between Terminals:

0.490 mils and 0.510 centimeters

Drive Level Rating:

Between 27.0 milliwatts and 33.0 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

Equivalent Resistance Value In Ohms:

60.0

Style Designator:

Oval body, pin terminals

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

NSN 5955-00-493-1060

Quartz Crystal Unit - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A059a0