NSN 5955-00-493-5894

Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-493-5894 | | | | |
|---|--|--|--|--|
| Overall Length: | | | | |
| 1.922 inches | | | | |
| Terminal Length: | | | | |
| 0.640 inches | | | | |
| Overall Width: | | | | |
| 1.170 inches | | | | |
| Body Length: | | | | |
| 1.282 inches | | | | |
| Body Width: | | | | |
| 1.125 inches | | | | |
| Body Thickness: | | | | |
| 0.411 inches | | | | |
| Overall Thickness: | | | | |
| 0.460 inches | | | | |
| Terminal Diameter: | | | | |
| 0.125 inches | | | | |
| Mode Of Oscillation: | | | | |
| Fundamental | | | | |
| Circuit Resonance: | | | | |
| Antiresonance | | | | |
| Load Capacitance In Picofarads: | | | | |
| Between 35.0 and 34.5 and 35.5 | | | | |
| Specified Frequency: | | | | |
| 7.02778 megahertz | | | | |
| Holder Cover Material: | | | | |
| Metal | | | | |
| Operating Tempurature Range: | | | | |
| -55.0/+90.0 degrees celsius | | | | |
| Center To Center Distance Between Terminals: | | | | |
| 0.500 inches | | | | |
| Drive Level Rating: | | | | |
| 30.0 milliwatts | | | | |
| Frequency Tolerance For Operating Tempurature In Percent: | | | | |
| -0.005/+0.005 | | | | |
| Equivalent Resistance Value In Ohms: | | | | |
| 50.0 | | | | |
| Style Designator: | | | | |
| Oval body, pin terminals | | | | |
| Test Data Document: | | | | |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification | | | | |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain | | | | |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/76 government specification

NSN 5955-00-493-5894

Quartz Crystal Unit - Page 2 of 2



| She | lf | I if | ρ. |
|-----|-----|------|----|
| ~ | ••• | | • |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0