Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-498-6473

| Overall Length: |
|---|
| Between 1.600 inches and 1.780 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| Between 1.470 inches and 1.530 inches |
| Environmental Protection: |
| Shock resistant and vibration |
| Vibration Resistance Range In Hertz: |
| +20.0 to 2000.0 |
| Shock Resistance Rating In Gravitational Units: |
| 45.0 |
| Operating Tempurature Range: |
| -55.0 to 125.0 degrees celsius |
| Average Life Rating: |
| 2000.0 |
| Average Life Measurement: |
| Hours |
| Average Life Rating In Hours: |
| 2000.0 |
| Basic Shape Style: |
| Rectangular or square |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Mechanical |
| Control Type: |
| Remote |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 4.0 megahertz operating channel |
| Average Power Rating Per Channel: |
| 350.0 milliwatts input |
| Shock Pulse Duration Time: |
| 3.0 milliseconds |
| Connection Type And Location: |
| Solder lug front |
| Connection Contact Type And Quantity: |
| 4 solder lug external |
| |

Crystal Controlled Oscillator - Page 2 of 2



External Dc Operating Voltage In Volts:

12.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200