## NSN 5955-00-511-4047

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-511-4047
Overall Length:
1.774 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
1.526 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 19.5 and 20.5
Shunt Capacitance In Picofarads:
6.5
Specified Frequency:
41.600 kilohertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+70.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
0.1 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.012/+0.012
Equivalent Resistance Value In Ohms:
110000.0
Test Data Document:
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

## NSN 5955-00-511-4047

Quartz Crystal Unit - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıı	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A059a0