NSN 5955-00-538-7233

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-538-7233

Overall Length:
1.023 inches
Terminal Length:
0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.170 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Frequency Tolerance At Reference Tempurature In Percent:
-0.007/+0.007
-0.007/+0.007
Frequency Stability In Percent:
Frequency Stability In Percent:
Frequency Stability In Percent: -0.0005/+0.0005
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Drive Level Rating:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Drive Level Rating: Between 1.0 milliwatts and 0.8 milliwatts and 1.2 milliwatts
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Drive Level Rating: Between 1.0 milliwatts and 0.8 milliwatts and 1.2 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
Frequency Stability In Percent: -0.0005/+0.0005 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: -55.0/+90.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Drive Level Rating: Between 1.0 milliwatts and 0.8 milliwatts and 1.2 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002

Style Designator:

Oval body, pin terminals

NSN 5955-00-538-7233

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0