# NSN 5955-00-554-8845

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-554-8845

# **Overall Length:**

1.023 inches

# **Terminal Length:**

Between 0.223 inches and 0.248 inches

# **Overall Width:**

0.757 inches

#### **Body Length:**

0.775 inches

#### **Body Width:**

0.725 inches

#### Body Thickness:

0.317 inches

#### **Overall Thickness:**

0.352 inches

#### **Terminal Diameter:**

Between 0.048 inches and 0.052 inches

## Mode Of Oscillation:

Third overtone

#### **Circuit Resonance:**

Series resonance

# Shunt Capacitance In Picofarads:

7.0

## Specified Frequency:

41.781481 megahertz

### Frequency Tolerance At Reference Tempurature In Percent:

-0.001/+0.001

### Frequency Stability In Percent:

-0.00025/+0.00025

### **Controlled Reference Temp:**

75.0 degrees celsius

### **Operable Tempurature Range:**

-55.0/+90.0 degrees celsius

#### Holder Cover Material:

Metal

### **Operating Tempurature Range:**

+70.0/+80.0 degrees celsius

# Center To Center Distance Between Terminals:

0.478 mils and 0.494 centimeters

# **Drive Level Rating:**

Between 0.8 milliwatts and 1.2 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

# NSN 5955-00-554-8845

Quartz Crystal Unit - Page 2 of 2



# Equivalent Resistance Value In Ohms:

40.0

## Style Designator:

Oval body, pin terminals

### Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A059a0