

NSN 5955-00-573-8083 Crystal Controlled Oscillator - Page 1 of 2	AeroBas Gro
View Online at https://aerobasegroup.com/nsn/5955-00-573-8083	
Overall Width:	
8.062 inches	
Environmental Protection:	
General purpose	
Vibration Resistance Range In Hertz:	
+5.0/+25.0	
Shock Resistance Rating In Gravitational Units:	
50.0	
Operating Tempurature Range:	

+0.0/+60.0 degrees celsius **Average Life Measurement:**

Operating Control Method:

Circuit Construction Type:

Switching Rate Per Second:

Frequency Per Channel:

529.0 kilohertz operating channel Frequency Adjustment Type:

Distortion Type And Percent:

Shock Pulse Duration Time:

Variation Frequency Rating In Decibels:

Maximum Continuous Operating Time In Hours:

Installation Design:

Basic Shape Style: Rectangular or square **Identification Designator:**

1603341-56232 Inclosure Type:

Encased

Automatic

Mechanical **Control Type:**

Solid state

Continuous

1.6 amplitude

11.0 milliseconds

10000.0

37.0

Frequency Shift: 31.7 kilohertz

Local

4960

Not rated

NSN 5955-00-573-8083

Crystal Controlled Oscillator - Page 2 of 2



Connection Ty	pe And l	Location:
---------------	----------	-----------

Receptacle, power rear

Connection Contact Type And Quantity:

2 receptacle, power external

External Dc Operating Voltage In Volts:

30.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200