

View Online at <https://aerobasegroup.com/nsn/5955-00-573-8083>

Overall Width:

8.062 inches

Environmental Protection:

General purpose

Vibration Resistance Range In Hertz:

+5.0/+25.0

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Identification Designator:

1603341-56232

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Local

Circuit Construction Type:

Solid state

Switching Rate Per Second:

4960

Frequency Shift:

31.7 kilohertz

Frequency Per Channel:

529.0 kilohertz operating channel

Frequency Adjustment Type:

Continuous

Variation Frequency Rating In Decibels:

37.0

Distortion Type And Percent:

1.6 amplitude

Maximum Continuous Operating Time In Hours:

10000.0

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, power rear

Connection Contact Type And Quantity:

2 receptacle, power external

External Dc Operating Voltage In Volts:

30.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200