Crystal Controlled Oscillator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-00-575-8012

Overall Length:         1.500 inches         Overall Width:         1.500 inches         Overall Width:         1.500 inches         Environmental Protection:         Corresion resistant         Operating Tempurature Range:         +0.04-70.0 degrees celsius         Average Life Measurement:         Not rated         Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Solid state         Frequency Per Channel:         10.00 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Contact Type And Quantity:         4 solef lug external         Sheff Life:         Na         Uht Of Measure:         ·         Permilliarization:         Na         Data Elementa El	
Overall Height:0.800 inchesOverall Width:1.500 inchesEnvironmental Protection:Corrosion resistantOperating Tempurature Range:+0.04-70.0 degrees celsiusAverage Life Measurement:Not ratedBasic Shape Style:Rectangular or squareInclosure Type:EncasedOperating Control Method:ManualInstallation Design:ModuleConcoir Type:LocalSolid stateFrequency Per Channel:100.0 megahertz output channelSignal Voltage Rating Per Channel:100.0 megahertz output channel100.0 megahertz output channel	Overall Length:
0.800 inches  Verail Width: 1.500 inches  Environmental Protection: Corrosion resistant  Operating Tempurature Range: 4.0.0/*0.0 degrees celsius  Average Life Measurement: Not rated  Basic Shape Style: Rectangular or square Inclosure Type: Rectangular or square Inclosure Type: Rectangular or square Corporting Control Method: Manual Installation Design: Rectangular control Method: Control Type: Solid state Frequency Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom  Connection Type And Quantity: A solder lug external  Suef Life: Na  Partial Construction Type And Quantity: A solder lug external  Partial Construction  Printed circuit bottom  Connection Contact Type And Quantity: A solder lug external  Partial Content Contact Type And Quantity: A solder lug external  Partial Content Contact Type And Quantity: A solder lug external  Partial Contact Type And Partial And Partial And Partial And Partial A	
Overall Width:         1.500 inches         Environmental Protection:         Correstion resistant         Operating Tempurature Range:         +0.0470.0 degrees celsius         Average Life Measurement:         Not rated         Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Chront Type:         Solid state         Frequency Per Channel:         10.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Location:         Printed circuit bottom         Connection Contat Type And Quantity:         4 solder lug external         Shelf Life:         Iva         Tord Measure:         Iva         Denlitarization:         Iva         Iva         Iva         Iva         Iva         Iva         Iva         Iva         Iva      Iva      Iva </th <th></th>	
1.500 inches Environmental Protection: Corrosion resistant Operating Tempurature Range: +0.047.0.0 degrees celsius Average Life Measurement: +0.047.0.0 degrees celsius Average Life Measurement: Not rated Basic Shape Style: Rectangular or square Inclosure Type: Encased Operating Control Method: Manual Installation Design: Kodule Control Type: Local Control Type: Solid state Frequency Per Channel: Solid state Frequency Per Channel: Solod volts input Connection Type And Location: Printed circuit bottom Asolder lug external Shef Life: Na	
Environmental Protection:   Corrosion resistant   Operating Tempurature Range:   40.04-70.0 degrees celsius   Average Life Measurement:   Not rated   Basic Shape Style:   Rectangular or square   Inclosure Type:   Encased   Operating Control Method:   Manual   Installation Design:   Module   Control Type:   Local   Solid State   Frequency Per Channel:   Solod State   Solod State   Solod State   Frequency Per Channel:   Solod State   Funcet Control Type And Location:   Printed circuit bottom   Module   Contection Type And Location:   Printed circuit Dottom   Printed circuit Dottom   Contection Type And Location:   Printed circuit Dottom   Printed circuit Dottom   Contection Type And Location:   Printed circuit Dottom   Contection Type And Location:   Printed circuit Dottom   Contection Type And Location:   Printed circuit Dottom   Frequency Per Channel:   Solod State   Frequency Per Channel:   Contection Type And Location:   Printed circuit Dottom <td< th=""><th>Overall Width:</th></td<>	Overall Width:
Corrosion resistant  Poperating Tempurature Range: +0.01+70.0 degrees celsius  Average Life Measurement: Not rated  Basic Shape Style: Rectangular or square  Inclosure Type: Encased  Operating Control Method: Annual  Installation Design:  Andule  Control Type: Local  Control Type: Solid state  Frequency Per Channel: Solid state  Signal Vottage Rating Per Channel: Solod state  Connection Type And Location: Printed circuit bottom  Connection Type And Quantity: Adoler lag external  Sheff Life: Na  Anual  Installation  Solid state  Connection Type And Quantity: Adoler lag external  Sheff Life: Na  Anual  Frequency Per Channel: Adoler lag external  Sheff Life: Na  Anual  Frequency Per Channel: Adoler lag external  Sheff Life: Na  Anual  Frequency Per Channel: Adoler lag external  Sheff Life: Na  Anual	1.500 inches
Operating Tempurature Range:         +0.0/+70.0 degrees celsius         Average Life Measurement:         Not rated         Basic Shape Style:         Retangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Solid state         Frequency Per Channel:         10.0.0 megahertz output channel         Signal Vottage Rating Per Channel:         5.200 volts input         Connection Type And Location:         Printed circuit bottom         Connection Contact Type And Quantity:         4 solder lug external         Shelf Life:         Na         Two         Frequency Per Inter Contant Type And Quantity:         A solder lug external         Shelf Life:         Na         Builder Life:         Na         Solider lug external         Frequency Per And Quantity:         A solder lug external         Shelf Life:         Na         Builder Life:         Na	Environmental Protection:
<ul> <li>+0.0/+70.0 degrees celsius</li> <li>Average Life Measurement:</li> <li>Not rated</li> <li>Basic Shape Style:</li> <li>Rectangular or square.</li> <li>Inclosure Type:</li> <li>Encased</li> <li>Operating Control Method:</li> <li>Manual</li> <li>Installation Design:</li> <li>Module</li> <li>Control Type:</li> <li>Local</li> <li>Control Type:</li> <li>Solid state</li> <li>Frequency Per Channel:</li> <li>Soloy oths input</li> <li>Connection Type And Location:</li> <li>Printed circuit bottom</li> <li>Printed circuit bottom</li> <li>Andue interference</li> <li>A solder lug external</li> <li>Sheff Life:</li> <li>N/a</li> <li>Interference</li> <li>Frequency Per Channel:</li> <li>Soloy oths input</li> <li>Connection Type And Quantity:</li> <li>A solder lug external</li> <li>Sheff Life:</li> <li>N/a</li> <li>Fig:</li> <li>Solid State</li> </ul>	Corrosion resistant
Average Life Measurement:         Not rated         Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Control Type:         Solid State         Frequency Per Channel:         100.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Quantity:         4 solder lug external         Sheff Life:         N/a         Encilier Consertion Type And Quantity:         A solder lug external         Frequency Per Channel:         10.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Quantity:         4 solder lug external         Inti Of Measure:         Na         Pinted rizetion:         Na         Fig:	Operating Tempurature Range:
Not rated Basic Shape Style: Rectangular or square Rectangular or square Inclosure Type: Encased Derating Control Method: Manual Installation Design: Module Control Type: Local Control Type: Local Control Type: Local Signal Voltage Rating Per Channel: Signal Vo	+0.0/+70.0 degrees celsius
Basic Shape Style:         Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Circuit Construction Type:         Solid state         Frequency Per Channel:         10.0.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Printed circuit bottom         Printed circuit bottom         Solider lug external         Shelf Life:         Iva         Iva         Printed circuit bottom         Foreinerine Context Type And Quantity:         Iva         Dider lug external         Shelf Life:         Iva         Printed circuit bottom         Iva         Dider lug external         Shelf Life:         Iva         Printed circuit bottom         Fig:         Iva         Iva         Iva         Iva         Iva         Iva         Iva <tr< th=""><th>Average Life Measurement:</th></tr<>	Average Life Measurement:
Rectangular or square         Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Circuit Construction Type:         Solid state         Frequency Per Channel:         10.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Location:         Printed circuit bottom         Context Type And Quantity:         4 solder lug external         Shelf Life:         N/a         Dini Of Measure:	Not rated
Inclosure Type:         Encased         Operating Control Method:         Manual         Installation Design:         Module         Control Type:         Local         Circuit Construction Type:         Solid state         Frequency Per Channel:         100.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Location:         Printed circuit bottom         Connection Contact Type And Quantity:         4 solder lug external         Shelf Life:         Iv/a         Init of Measure:         -         Demilitarization:         No         Fig:	Basic Shape Style:
Encased Qperating Control Method: Manual Installation Design: Module Control Type: Local Circuit Construction Type: Solid state Frequency Per Channel: Solid state Frequency Per Channel: Signal Voltage Rating Per Channel: Signal Volta	Rectangular or square
Operating Control Method:ManualInstallation Design:ModuleControl Type:LocalCircuit Construction Type:Solid stateFrequency Per Channel:100.0 megahertz output channelSignal Voltage Rating Per Channel:5.200 volts inputPrinted circuit bottomPrinted circuit bottomSolider Life:N/aSolider Life:N/aDemiltarization:-FrequenciesFig:NoFig:Fig:	Inclosure Type:
Manual Installation Design: Installation Design: Installation Design: Installation Design: Installation Design: Installation Design: Installation Type: Installation Install	Encased
Installation Design: Module Control Type: Local Circuit Construction Type: Solid state Frequency Per Channel: 100.0 megahertz output channel Signal Voltage Rating Per Channel: S.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Dit of Measure:  Fig:	Operating Control Method:
Module Control Type: Local Circuit Construction Type: Solid state Frequency Per Channel: 100.0 megahertz output channel Signal Voltage Rating Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Manual
Control Type:LocalCircuit Construction Type:Solid stateFrequency Per Channel:100.0 megahertz output channelSignal Voltage Rating Per Channel:5.200 volts inputConnection Type And Location:Printed circuit bottomConnection Contact Type And Quantity:4 solder lug externalShelf Life:NaUnit Of Measure:Poinlitarization:NoFig:	Installation Design:
Local Circuit Construction Type: Cold state Frequency Per Channel: 100.0 megahertz output channel Signal Voltage Rating Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Module
Circuit Construction Type:Solid stateFrequency Per Channel:100.0 megahertz output channelSignal Voltage Rating Per Channel:5.200 volts inputConnection Type And Location:Printed circuit bottomConnection Contact Type And Quantity:4 solder lug externalShelf Life:N/aUnit Of Measure:NoFing:	Control Type:
Solid state Frequency Per Channel: 100.0 megahertz output channel Signal Voltage Rating Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure: Foenilitarization: No Fig:	Local
Frequency Per Channel:         100.0 megahertz output channel         Signal Voltage Rating Per Channel:         5.200 volts input         Connection Type And Location:         Printed circuit bottom         Connection Contact Type And Quantity:         4 solder lug external         Shelf Life:         Iv/a         Demilitarization:         Iv/a         Frequencing         Fig:	Circuit Construction Type:
100.0 megahertz output channel Signal Voltage Rating Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Dit Of Measure:  Fig:	Solid state
Signal Voltage Rating Per Channel: 5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Frequency Per Channel:
5.200 volts input Connection Type And Location: Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	100.0 megahertz output channel
Connection Type And Location:Printed circuit bottomConnection Contact Type And Quantity:4 solder lug externalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Signal Voltage Rating Per Channel:
Printed circuit bottom Connection Contact Type And Quantity: 4 solder lug external Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	5.200 volts input
Connection Contact Type And Quantity:4 solder lug externalShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Connection Type And Location:
4 solder lug external Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Printed circuit bottom
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	Connection Contact Type And Quantity:
N/a Unit Of Measure:  Demilitarization: No Fiig:	4 solder lug external
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A32200	Fiig:
	A32200