Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-589-1125

Overall Length:
1.750 inches
Overall Height:
0.650 inches
Overall Width:
1.210 inches
Vibration Resistance Range In Hertz:
Not rated
Shock Resistance Rating In Gravitational Units:
15.0
Operating Tempurature Range:
-0.0 to 55.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
Not rated
Inclosure Type:
Encased
Installation Design:
Module
Circuit Construction Type:
Solid state
Frequency Per Channel:
7.0 megahertz output channel
Attenuation In Decibels:
Not rated
Average Power Rating Per Channel:
100.0 milliwatts input
Signal Voltage Rating Per Channel:
5.000 volts input
Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Distortion Type And Percent:
10.0 frequency
Maximum Continuous Operating Time In Hours:
Not rated
Connection Type And Location:
Printed circuit bottom

NSN 5955-00-589-1125

Crystal Controlled Oscillator - Page 2 of 2



Connection Contact Type And Quantity:

1 printed circuit external

External Dc Operating Voltage In Volts:

5.0 single voltage

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A32200