## NSN 5955-00-601-6271

Crystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-00-601-6271



**Overall Length:** 0.750 inches **Overall Height:** 0.565 inches **Overall Width:** 0.470 inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** +5.0 to 55.0 **Vibration Resistance Amplitude:** 15.0 inches total excursion **Shock Resistance Rating In Gravitational Units:** 40.0 **Operating Tempurature Range:** +0.0 to 70.0 degrees celsius **Average Life Rating:** 1000.0 **Average Life Measurement:** Hours **Average Life Rating In Hours:** 1000.0 **Basic Shape Style:** Rectangular or square **Identification Designator:** K1091a8-1900mhz-01537 **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased Installation Design: **Circuit Construction Type:** Solid state Frequency Per Channel: 8.19 megahertz output channel **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** Not rated **Signal Voltage Rating Per Channel:** Not rated

NSN 5955-00-601-6271 Crystal Controlled Oscillator - Page 2 of 2



Overall Gain:
Not rated
Impedance Rating Per Channel:
Not rated
Maximum Continuous Operating Time In Hours:
Not rated
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Wire lead terminals bottom
Connection Contact Type And Quantity:
14 wire lead terminals external
External Dc Operating Voltage In Volts:
5.0 single voltage
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A32200