

View Online at <https://aerobasegroup.com/nsn/5955-00-615-0160>

Overall Length:

0.530 inches

Terminal Length:

0.5003 inches

Overall Width:

0.435 inches

Body Width:

0.402 inches

Body Thickness:

0.150 inches

Overall Thickness:

0.183 inches

Terminal Diameter:

Between 0.015 inches and 0.019 inches

Mode Of Oscillation:

Fifth overtone and third overtone

Circuit Resonance:

Series resonance

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

103.9667 megahertz

Holder Cover Material:

Metal or glass

Operating Temperature Range:

-55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius

Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

Drive Level Rating:

Between 1.6 milliwatts and 2.4 milliwatts

Frequency Tolerance For Operating Temperature In Percent:

-0.005/+0.005 and -0.0010/+0.0010

Equivalent Resistance Value In Ohms:

60.0

Style Designator:

Rectangular body, gull wing

Test Data Document:

81349-mil-c-3098/38 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/83 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A059a0