## NSN 5955-00-682-2676

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-682-2676

Overall Length:

0.530 inches

**Terminal Length:** 

0.5003 inches

## Overall Width:

0.435 inches

#### Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.015 inches and 0.019 inches

### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

## Load Capacitance In Picofarads:

Between 31.5 and 32.5

## Shunt Capacitance In Picofarads:

7.0

#### **Specified Frequency:**

8.725 megahertz

## Holder Cover Material:

Metal or glass

### **Operating Tempurature Range:**

-40.0/+85.0 degrees celsius

### **Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 8.0 milliwatts and 12.0 milliwatts

### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005 and -0.0010/+0.0010

### **Equivalent Resistance Value In Ohms:**

35.0

## Style Designator:

Rectangular body, gull wing

### **Test Data Document:**

81349-mil-c-3098/38 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-3098/72 government specification

# NSN 5955-00-682-2676

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

