NSN 5955-00-682-2690

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-682-2690

Overall Length:				
0.530 inches				
Terminal Length:				
0.5003 inches				
Overall Width:				
0.435 inches				
Body Width:				
0.402 inches				
Body Thickness:				
0.150 inches				
Overall Thickness:				
0.183 inches				
Terminal Diameter:				
Between 0.015 inches and 0.019 inches				
Mode Of Oscillation:				
Fundamental				
Circuit Resonance:				
Antiresonance				
Load Capacitance In Picofarads:				
Between 31.5 and 32.5				
Shunt Capacitance In Picofarads:				
7.0				
Specified Frequency:				
9.425 megahertz				
Holder Cover Material:				
Metal or glass				
Operating Tempurature Range:				
-40.0/+85.0 degrees celsius				
Center To Center Distance Between Terminals:				
0.184 mils and 0.200 centimeters				
Drive Level Rating:				
Between 8.0 milliwatts and 12.0 milliwatts				
Frequency Tolerance For Operating Tempurature In Percent:				
-0.005/+0.005 and -0.0010/+0.0010				
Equivalent Resistance Value In Ohms:				
35.0				
Style Designator:				
Rectangular body, gull wing				
Test Data Document:				
81349-mil-c-3098/38 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/72 government specification

NSN 5955-00-682-2690

Quartz Crystal Unit - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0