## NSN 5955-00-709-3967

Quartz Crystal Unit - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5955-00-709-3967

1.023 inches	
Terminal Length:	
0.238 inches	
Overall Width:	
0.757 inches	
Body Length:	
0.775 inches	
Body Width:	
0.725 inches	
Body Thickness:	
0.317 inches	
Overall Thickness:	
0.352 inches	
Terminal Diameter:	
0.050 inches	
Mode Of Oscillation:	
Fundamental	
Circuit Resonance:	
Antiresonance	
Load Capacitance In Picofarads:	
Between 32.0 and 31.5 and 32.5	
Shunt Capacitance In Picofarads:	
7.0	
Specified Frequency:	
8.275 megahertz	
Holder Cover Material:	
Metal	
Operating Tempurature Range:	
-55.0/+105.0 degrees celsius	
Center To Center Distance Between Terminals:	
0.486 inches	
Drive Level Rating:	
Between 10.0 milliwatts and 8.0 milliwatts and 12.0 milliwatts	
Frequency Tolerance For Operating Tempurature In Percent:	
-0.005/+0.005	
Equivalent Resistance Value In Ohms:	
24.0	
Style Designator:	
Oval body, pin terminals	
Test Data Document:	

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-00-709-3967

Quartz Crystal Unit - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0