NSN 5955-00-709-4328

Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-709-4328 |
|---|
| Overall Length: |
| 1.023 inches |
| Terminal Length: |
| Between 0.223 inches and 0.248 inches |
| Overall Width: |
| 0.757 inches |
| Body Length: |
| 0.775 inches |
| Body Width: |
| 0.725 inches |
| Body Thickness: |
| 0.317 inches |
| Overall Thickness: |
| 0.352 inches |
| Terminal Diameter: |
| Between 0.048 inches and 0.052 inches |
| Mode Of Oscillation: |
| Third overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 42.59259 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.478 mils and 0.494 centimeters |
| Drive Level Rating: |
| Between 1.6 milliwatts and 2.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 40.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/30 government specification

NSN 5955-00-709-4328

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0