NSN 5955-00-709-5764

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-709-5764		
Overall Length:		
1.023 inches		
Terminal Length:		
Between 0.223 inches and 0.248 inches		
Overall Width:		
0.757 inches		
Body Length:		
0.775 inches		
Body Width:		
0.725 inches		
Body Thickness:		
0.317 inches		
Overall Thickness:		
0.352 inches		
Terminal Diameter:		
Between 0.048 inches and 0.052 inches		
Mode Of Oscillation:		
Fundamental		
Circuit Resonance:		
Antiresonance		
Load Capacitance In Picofarads:		
Between 31.5 and 32.5		
Shunt Capacitance In Picofarads:		
7.0		
Specified Frequency:		
6.516666 megahertz		
Holder Cover Material:		
Metal		
Operating Tempurature Range:		
-55.0/+105.0 degrees celsius		
Center To Center Distance Between Terminals:		
0.478 mils and 0.494 centimeters		
Drive Level Rating:		
Between 8.0 milliwatts and 12.0 milliwatts		
Frequency Tolerance For Operating Tempurature In Percent:		
-0.005/+0.005		
Equivalent Resistance Value In Ohms:		
35.0		
Style Designator:		
Oval body, pin terminals		
Test Data Document:		

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-709-5764

Quartz Crystal Unit - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0