## NSN 5955-00-726-6164

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-726-6164

**Overall Length:** 

Between 0.973 inches and 1.023 inches

**Terminal Length:** 

Between 0.223 inches and 0.248 inches

**Overall Width:** 

0.757 inches

**Body Length:** 

Between 0.750 inches and 0.775 inches

**Overall Thickness:** 

0.352 inches

**Terminal Diameter:** 

Between 0.048 inches and 0.052 inches

Mode Of Oscillation:

Fifth overtone and third overtone

**Circuit Resonance:** 

Series resonance

**Shunt Capacitance In Picofarads:** 

3.0

**Specified Frequency:** 

66.100 megahertz

**Controlled Reference Temp:** 

75.0 degrees celsius

**Operable Tempurature Range:** 

-55.0/+70.0 degrees celsius

**Holder Cover Material:** 

Metal or glass

**Operating Tempurature Range:** 

+70.0/+80.0 degrees celsius and -55.0/+90.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.478 mils and 0.494 centimeters

**Drive Level Rating:** 

Between 0.8 milliwatts and 1.2 milliwatts

**Frequency Tolerance For Operating Tempurature In Percent:** 

-0.0005/+0.0005

**Equivalent Resistance Value In Ohms:** 

40.0

Style Designator:

Round body, ferrule terminals

**Test Data Document:** 

81349-milc3098b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

## NSN 5955-00-726-6164

Quartz Crystal Unit - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A059a0