# NSN 5955-00-762-1528

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-762-1528

# **Overall Length:**

0.778 inches

## **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.435 inches

## **Body Length:**

0.530 inches

## **Body Width:**

0.402 inches

## Body Thickness:

0.150 inches

## **Overall Thickness:**

0.183 inches

## Terminal Diameter:

Between 0.048 inches and 0.052 inches

## Mode Of Oscillation:

Third overtone

## **Circuit Resonance:**

Series resonance

## Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

54.150 megahertz

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

-40.0/+105.0 degrees celsius

## **End Application:**

Instrument landing system, local/gs/beacon, fa800 (mark1)

## **Center To Center Distance Between Terminals:**

0.486 inches

#### **Drive Level Rating:**

Between 1.6 milliwatts and 2.4 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.003/+0.003

## Equivalent Resistance Value In Ohms:

40.0

# Style Designator:

Oval body, pin terminals

# **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5955-00-762-1528

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

