## NSN 5955-00-813-6397

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-813-6397

**Overall Length:** 

1.774 inches

**Terminal Length:** 

Between 0.223 inches and 0.238 inches

**Overall Width:** 

0.757 inches

**Body Length:** 

1.526 inches

**Body Width:** 

0.725 inches

Body Thickness:

0.317 inches

**Overall Thickness:** 

0.352 inches

**Terminal Diameter:** 

Between 0.048 inches and 0.050 inches

Mode Of Oscillation:

Fundamental

**Circuit Resonance:** 

Antiresonance

Load Capacitance In Picofarads:

Between 20.0 and 19.5 and 20.5

Shunt Capacitance In Picofarads:

Between 4.7 and 4.0 and 5.4

**Specified Frequency:** 

128.000 kilohertz

Holder Cover Material:

Metal

**Operating Tempurature Range:** 

-40.0/+70.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.478 mils and 0.486 centimeters

**Drive Level Rating:** 

Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.020/+0.020

Equivalent Resistance Value In Ohms:

5000.0

Style Designator:

Oval body, pin terminals

## **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-00-813-6397

Quartz Crystal Unit - Page 2 of 2

**Specification Data:** 

81349-milc3098 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

