## NSN 5955-00-848-6542

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-848-6542 **Overall Height: 4.313** inches **Overall Width:** 1.500 inches **Environmental Protection:** General purpose **Vibration Resistance Range In Hertz:** +15.0/+55.0 **Vibration Resistance Amplitude:** 0.015 inches total excursion **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 12000.0 feet **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Electron tube Frequency Per Channel: 395.0 hertz output channel **Average Power Rating Per Channel:** 10.0 milliwatts output

Impedance Rating Per Channel: 500.000 kilohms output channel **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Solder lug bottom **Operating Ac Frequency In Hertz:** 60.0 single voltage **Connection Contact Type And Quantity:** 5 solder lug external **External Dc Operating Voltage In Volts:** 250.0 single voltage

## NSN 5955-00-848-6542

Noncrystal Controlled Oscillator - Page 2 of 2



## **External Ac Operating Voltage In Volts:**

6.3 single voltage

Phase:

Single

**Fsc Application Data:** 

Simulator, radar signal

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200