NSN 5955-00-851-2897

Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-851-2897 |
|---|
| Overall Length: |
| 1.937 inches |
| Terminal Length: |
| Between 0.625 inches and 0.655 inches |
| Overall Height: |
| 1.170 inches |
| Overall Width: |
| Between 1.090 inches and 1.170 inches |
| Body Length: |
| 1.282 inches |
| Body Width: |
| 1.125 inches |
| Body Thickness: |
| 0.411 inches |
| Overall Thickness: |
| 0.460 inches |
| Terminal Diameter: |
| Between 0.123 inches and 0.127 inches |
| Mode Of Oscillation: |
| Fundamental |
| Circuit Resonance: |
| Antiresonance |
| Load Capacitance In Picofarads: |
| Between 34.5 and 35.5 |
| Specified Frequency: |
| 8.520 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0/+90.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.490 mils and 0.510 centimeters |
| Drive Level Rating: |
| Between 27.0 milliwatts and 33.0 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 30.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-851-2897

Quartz Crystal Unit - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0