NSN 5955-00-889-3082

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-889-3082 **Overall Length:** 0.530 inches **Terminal Length:** 0.5003 inches **Overall Width:** 0.435 inches **Body Width:** 0.402 inches **Body Thickness:** 0.150 inches **Overall Thickness:** 0.183 inches **Circuit Resonance:** Series resonance **Shunt Capacitance In Picofarads:** 7.0 **Specified Frequency:** 60.734 megahertz **Holder Cover Material:** Metal or glass **Operating Tempurature Range:** -55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius **Center To Center Distance Between Terminals:** 0.184 mils and 0.200 centimeters **Drive Level Rating:** Between 1.5 milliwatts and 2.4 milliwatts **Frequency Tolerance For Operating Tempurature In Percent:** -0.005/+0.005 and -0.0010/+0.0010 **Equivalent Resistance Value In Ohms:** 50.0 **Style Designator:** Rectangular body, gull wing **Test Data Document:** 81349-mil-c-3098/38 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-3098/34 government specification Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5955-00-889-3082

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0