# NSN 5955-00-889-4248

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-889-4248

**Overall Length:** 

1.023 inches

**Terminal Length:** 

Between 0.223 inches and 0.248 inches

**Overall Width:** 

0.757 inches

**Body Length:** 

0.775 inches

**Body Width:** 

0.725 inches

Body Thickness:

0.317 inches

**Overall Thickness:** 

0.352 inches

Terminal Diameter:

Between 0.048 inches and 0.052 inches

Mode Of Oscillation:

Fundamental

**Circuit Resonance:** 

Antiresonance

Load Capacitance In Picofarads:

Between 31.5 and 32.5

Shunt Capacitance In Picofarads:

7.0

**Specified Frequency:** 

5.15625 megahertz

Frequency Tolerance At Reference Tempurature In Percent:

-0.007/+0.007

**Frequency Stability In Percent:** 

-0.0005/+0.0005

**Controlled Reference Temp:** 

75.0 degrees celsius

**Operable Tempurature Range:** 

-55.0/+90.0 degrees celsius

Holder Cover Material:

Metal

**Operating Tempurature Range:** 

+70.0/+80.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.478 mils and 0.494 centimeters

**Drive Level Rating:** 

Between 4.0 milliwatts and 6.0 milliwatts

## NSN 5955-00-889-4248

Quartz Crystal Unit - Page 2 of 2



## Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002

Equivalent Resistance Value In Ohms:

35.0

Style Designator:

Oval body, pin terminals

## Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A059a0