NSN 5955-00-900-6850

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-900-6850

Overall Length:
Between 0.753 inches and 0.778 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.435 inches
Body Length:
0.530 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.038 inches and 0.042 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Specified Frequency:
11.025 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.002/+0.002
Frequency Stability In Percent:
-0.0001/+0.0001
Controlled Reference Temp:
85.0 degrees celsius
Operable Tempurature Range:
-55.0/+80.0 degrees celsius
Holder Cover Material:
Metal or glass
Operating Tempurature Range:
+83.0/+87.0 degrees celsius
Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

Drive Level Rating:

Between 2.0 milliwatts and 3.0 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.004/+0.004

NSN 5955-00-900-6850

Quartz Crystal Unit - Page 2 of 2



Equivalent Resistance	Value In	Ohms:
------------------------------	----------	-------

22.0

Style Designator:

Test Data Document:

81349-mil-c-3098/38 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/114 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A059a0