NSN 5955-00-900-9332

Quartz Crystal Unit - Page 1 of 2

81349-milc3098 government specification

Overall Length:



View Online at https://aerobasegroup.com/nsn/5955-00-900-9332

1.023 inches
Terminal Length:
0.238 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 19.5 and 20.5
Specified Frequency:
438.000 kilohertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Center To Center Distance Between Terminals:
0.486 inches
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.010/+0.010
Equivalent Resistance Value In Ohms:
8000.0
Style Designator:
Oval body, pin terminals
Test Data Document:
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:

NSN 5955-00-900-9332

Quartz Crystal Unit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0