## NSN 5955-00-910-8240

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-910-8240

#### **Overall Length:**

Between 0.500 inches and 0.525 inches

#### **Terminal Length:**

0.750 inches

## Overall Width:

Between 0.408 inches and 0.428 inches

#### **Body Width:**

Between 0.394 inches and 0.401 inches

#### **Body Thickness:**

Between 0.142 inches and 0.149 inches

#### **Overall Thickness:**

Between 0.156 inches and 0.176 inches

#### **Terminal Diameter:**

Between 0.016 inches and 0.019 inches

#### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

#### Load Capacitance In Picofarads:

Between 31.5 and 32.5

## Shunt Capacitance In Picofarads:

7.0

#### **Specified Frequency:**

12.247 megahertz

#### Holder Cover Material:

Metal or glass

#### **Operating Tempurature Range:**

-55.0/+105.0 degrees celsius and -55.0/+125.0 degrees celsius

#### Center To Center Distance Between Terminals:

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

#### Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005 and -0.0010/+0.0010

#### **Equivalent Resistance Value In Ohms:**

22.0

## Style Designator:

Rectangular body, gull wing

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5955-00-910-8240

Quartz Crystal Unit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A059a0

