NSN 5955-00-913-0734

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-913-0734 **Overall Length:** 5.250 inches **Overall Height:** 2.000 inches **Overall Width:** 2.000 inches **Vibration Resistance Range In Hertz:** +20.0/+500.0 **Shock Resistance Rating In Gravitational Units:** 15.0 **Operating Tempurature Range:** -30.0/+60.0 degrees celsius **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Installation Design:** Module **Circuit Construction Type:** Solid state Frequency Per Channel: 20.000 kilohertz output channel Signal Voltage Rating Per Channel: 1.000 volts output Impedance Rating Per Channel: 5.000 kilohms output channel **Maximum Continuous Operating Time In Hours:** 1440.0 **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Solder lug bottom **Operating Ac Frequency In Hertz:** 60.0 single voltage **Connection Contact Type And Quantity:** 8 solder lug external **External Dc Operating Voltage In Volts:** 25.0 single voltage **External Ac Operating Voltage In Volts:**

113.0 single voltage

NSN 5955-00-913-0734

Crystal Controlled Oscillator - Page 2 of 2



Phase:
Single
Fsc Application Data:
Radio set, except navigation, nonairborne
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A32200