# NSN 5955-00-914-0073

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-914-0073

**Overall Length:** 

1.023 inches

**Terminal Length:** 

0.238 inches

# **Overall Width:**

0.757 inches

Body Length:

0.775 inches

## **Body Width:**

0.725 inches

Body Thickness:

0.317 inches

## **Overall Thickness:**

0.352 inches

## **Terminal Diameter:**

## 0.050 inches

Mode Of Oscillation:

Fundamental

## Circuit Resonance:

Antiresonance

## Load Capacitance In Picofarads:

Between 20.0 and 19.5 and 20.5

# Specified Frequency:

455.000 kilohertz

## Frequency Tolerance At Reference Tempurature In Percent:

-0.002/+0.002

## Frequency Stability In Percent:

-0.0005/+0.0005

## **Controlled Reference Temp:**

75.0 degrees celsius

## **Operable Tempurature Range:**

-40.0/+70.0 degrees celsius

#### Holder Cover Material:

Metal

## **Operating Tempurature Range:**

+70.0/+80.0 degrees celsius

## Center To Center Distance Between Terminals:

0.486 inches

## **Drive Level Rating:**

Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts

# Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002

# NSN 5955-00-914-0073

Quartz Crystal Unit - Page 2 of 2



## Equivalent Resistance Value In Ohms:

8000.0

# Style Designator:

Oval body, pin terminals

## Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A059a0