## NSN 5955-00-916-9838

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-916-9838

| Overall Length:  |
|--|
| Between 0.723 inches and 0.773 inches  |
| Terminal Length:   |
| Between 0.223 inches and 0.248 inches  |
| Overall Width:   |
| Between 0.408 inches and 0.428 inches  |
| Body Length:   |
| Between 0.500 inches and 0.525 inches  |
| Body Width:  |
| Between 0.394 inches and 0.401 inches  |
| Body Thickness:  |
| Between 0.142 inches and 0.149 inches  |
| Overall Thickness:   |
| Between 0.166 inches and 0.176 inches  |
| Terminal Diameter:   |
| Between 0.038 inches and 0.042 inches  |
| Circuit Resonance:   |
| Series resonance   |
| Specified Frequency:   |
| 57.9667 megahertz  |
| Holder Cover Material:   |
| Metal or glass   |
| Operating Tempurature Range:   |
| +50.0/+90.0 degrees fahrenheit   |
| Center To Center Distance Between Terminals:   |
| 0.184 mils and 0.200 centimeters   |
| Drive Level Rating:  |
| Between 2.0 milliwatts and 3.0 milliwatts  |
| Frequency Tolerance For Operating Tempurature In Percent:  |
| -0.0005/+0.0005  |
| Equivalent Resistance Value In Ohms:   |
| 50.0   |
| Style Designator:  |
| Oval body, pin terminals   |
| Test Data Document:  |
| 00724-99-20810-249 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                      |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |

**Demilitarization:** Yes - demil/mli

## NSN 5955-00-916-9838

Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0