# NSN 5955-00-923-3650

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-923-3650

## **Overall Length:**

1.023 inches

### **Terminal Length:**

Between 0.223 inches and 0.248 inches

## **Overall Width:**

0.757 inches

#### **Body Length:**

0.775 inches

#### **Body Width:**

0.725 inches

#### Body Thickness:

0.317 inches

#### **Overall Thickness:**

0.352 inches

#### **Terminal Diameter:**

Between 0.048 inches and 0.052 inches

#### Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

### Load Capacitance In Picofarads:

Between 31.5 and 32.5

## Shunt Capacitance In Picofarads:

7.0

## **Specified Frequency:**

6.433333 megahertz

## Frequency Tolerance At Reference Tempurature In Percent:

-0.007/+0.007

## Frequency Stability In Percent:

-0.0005/+0.0005

## Controlled Reference Temp:

75.0 degrees celsius

## **Operable Tempurature Range:**

-55.0/+90.0 degrees celsius

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

+70.0/+80.0 degrees celsius

## Center To Center Distance Between Terminals:

0.478 mils and 0.494 centimeters

## **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

# NSN 5955-00-923-3650

Quartz Crystal Unit - Page 2 of 2



## Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002

**Equivalent Resistance Value In Ohms:** 

35.0

Style Designator:

Oval body, pin terminals

## **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A059a0