NSN 5955-00-923-8301

Quartz Crystal Unit - Page 1 of 2

Between 0.998 inches and 1.023 inches

Overall Length:



View Online at https://aerobasegroup.com/nsn/5955-00-923-8301

| Terminal Length: |
|---|
| Between 0.223 inches and 0.248 inches |
| Overall Width: |
| 0.757 inches |
| Body Length: |
| 0.775 inches |
| Overall Thickness: |
| 0.352 inches |
| Terminal Diameter: |
| Between 0.048 inches and 0.052 inches |
| Mode Of Oscillation: |
| Fifth overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 5.5 |
| Frequency Tolerance At Reference Tempurature In Percent: |
| -0.007/+0.007 |
| Frequency Stability In Percent: |
| -0.0002/+0.0002 |
| Controlled Reference Temp: |
| 75.0 degrees celsius |
| Operable Tempurature Range: |
| +0.0/+80.0 degrees celsius |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| +70.0/+80.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.478 mils and 0.494 centimeters |
| Drive Level Rating: |
| Between 1.8 milliwatts and 2.2 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.002/+0.002 |
| Equivalent Resistance Value In Ohms: |
| 40.0 |
| Style Designator: |
| Rectangular body, pin terminals |
| Test Data Document: |

10001-2521304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5955-00-923-8301

Quartz Crystal Unit - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0