NSN 5955-00-923-8304

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-923-8304

Overall Length:
1.023 inches
Terminal Length:
0.236 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
0.050 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
5.5
Frequency Tolerance At Reference Tempurature In Percent:
-0.0005/+0.0005
Frequency Stability In Percent:
-0.0002/+0.0002
-0.0002/+0.0002
-0.0002/+0.0002 Controlled Reference Temp:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 2.0 milliwatts and 1.8 milliwatts and 2.2 milliwatts
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 2.0 milliwatts and 1.8 milliwatts and 2.2 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
-0.0002/+0.0002 Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 2.0 milliwatts and 1.8 milliwatts and 2.2 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007
Controlled Reference Temp: 75.0 degrees celsius Operable Tempurature Range: +0.0/+80.0 degrees celsius Holder Cover Material: Metal Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: Between 2.0 milliwatts and 1.8 milliwatts and 2.2 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.002/+0.002 and -0.007/+0.007 Equivalent Resistance Value In Ohms:

Test Data Document:

10001-2521304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5955-00-923-8304

Quartz Crystal Unit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0